SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)
with its amendment Regulation (EU) 2015/830

KADOL ZBR

Date of issue : 06.10.2022
SDS No : ***130.01***
Revision date: -

1) IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name : KADOL ZBR
Product Form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Usage : Leather processing product

1.3. Details of the supplier of the safety data sheet

KDK KİMYA DERİ GIDA İNŞ.SAN.TİC.LTD.ŞTİ
İDOSB DİLEK SOK NO:6 X10 ÖZEL PARSEL K:1
TUZLA/ İSTANBUL
T +90 216 394 00 54
info@kdkkimya.com - www.kdkkimya.com

1.4. Emergency telephone number: No additional information available

2) HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Physicochemical	Not classified
Health	H319 - Eye Irrit. 2
Environmental	Not classified

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

GHS 07

Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash hands thoroughly after handling.
P280 Wear eye protection / face protection.
P337+P313 If eye irritation persists: Get medical advice / attention.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards
Information not available

3) COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances
Not applicable

3.2. Mixtures

Name	Product Identifier	%	1272/2008 (CLP)
2-BUTOXYETHANOL	CAS No: 111-76-2 EC No: 203-905-0 Index No: 603-014-00-0	≤ 2	H302 - Acute Tox. 4 H312 - Acute Tox. 4 H332 - Acute Tox. 4 H319 - Eye Irrit. 2 H315 - Skin Irrit. 2
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	CAS No: 68891-38-3 EC No: 500-234-8	≤ 1,25	H318 - Eye Dam. 1 H315 - Skin Irrit. 2 H412 - Aquatic Chronic 3
2,4-Pentanediol, 2-methyl-	CAS No: 107-41-5 EC No: 203-489-0	≤ 0,75	H315 - Skin Irrit. 2 H319 - Eye Irrit. 2
Poly(oxy-1,2-ethanediyl), α-isodecyl-ω-hydroxy-	CAS No: 61827-42-7 EC No: 612-519-5	≤ 0,75	H315 - Skin Irrit. 2 H319 - Eye Irrit. 2
White mineral oil (petroleum)	CAS No: 8042-47-5 EC No: 232-455-8	≤ 1,5	H304 - Asp. Tox. 1

Full text of H-statements: see section 16

4) FIRST AID MEASURES

4.1. Description of first aid measures
EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed
Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed
Information not available

5) FIREFIGHTING MEASURES

5.1. Extinguishing media
Suitable Extinguishing Equipment: The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
Unsuitable Extinguishing Equipment: None in particular.

5.2. Special hazards arising from the substance or mixture
Hazards Caused by Exposure in The Event of Fire:
Do not breathe combustion products.

5.3. Advice for firefighters
General Information
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

Special Protective Equipment for Fire-Fighters
Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6) ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures
Block the leakage if there is no hazard.
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions
The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up
Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections
Any information on personal protection and disposal is given in sections 8 and 13.

7) HANDLING AND STORAGE

7.1. Precautions for safe handling
Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Additional information on storage conditions:	BARREL-IBC
Storage and transportation temperature:	18/24 MONTHS CLOSED PACKAGING

7.3. Specific end use(s)
Information not available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006 (REACH)
with its amendment Regulation (EU) 2015/830

Date of issue : 06.10.2022
SDS No : ***130.01***

KADOL ZBR

Revision date: -

8) EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters
Regulatory References:

TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

2-BUTOXYETHANOL						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Legend: (C) = CEILING; INHAL= Inhalable Fraction; RESP= Respirable Fraction; THORA= Thoracic Fraction.

8.2. Exposure controls
As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.
Provide an emergency shower with face and eye wash station.

Hand Protection
Protect hands with category III work gloves (see standard EN 374).
The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Skin Protection
Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344).
Wash body with soap and water after removing protective clothing.

Eye Protection
Wear airtight protective goggles (see standard EN 166).

Respiratory Protection
If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

Environmental Exposure Controls
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9) PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Dark Brown
Odour	Characteristic
Odour threshold	Not available
pH	4,5 ± 0,5
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	Not available
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Explosive properties	Not available
Oxidizing properties	Not available

9.2. Other information
Information not available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006 (REACH)
with its amendment Regulation (EU) 2015/830

Date of issue : 06.10.2022
KADOL ZBR
SDS No : ***130.01*** Revision date: -

10) STABILITY AND REACTIVITY

10.1. Reactivity
There are no particular risks of reaction with other substances in normal conditions of use.
2-BUTOXYETHANOL: Decomposes under the effect of heat.

10.2. Chemical stability
The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions
No hazardous reactions are foreseeable in normal conditions of use and storage.
2-BUTOXYETHANOL: May react dangerously with: aluminum, oxidizing agents. Forms peroxides with: air.

10.4. Conditions to avoid
None in particular. However, the usual precautions used for chemical products should be respected.
2-BUTOXYETHANOL: Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials
Information not available

10.6. Hazardous decomposition products
2-BUTOXYETHANOL: May develop: hydrogen.

11) TOXICOLOGICAL INFORMATION

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information
Information not available

Information on likely routes of exposure
Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Information not available

Interactive effects
Information not available

Acute toxicity of the mixture:

2-BUTOXYETHANOL	
LD50 (Oral)	1200 mg/kg, Guinea pig
LC50 (Inhalation vapours)	2,2 mg/l/4h, Rat

Skin Corrosion / Irritation
Does not meet the classification criteria for this hazard class

Serious Eye Damage / Irritation
Causes serious eye irritation

Respiratory or Skin Sensitisation
Does not meet the classification criteria for this hazard class

Germ Cell Mutagenicity
Does not meet the classification criteria for this hazard class

Carcinogenicity
Does not meet the classification criteria for this hazard class

Reproductive Toxicity
Does not meet the classification criteria for this hazard class

STOT - Single Exposure
Does not meet the classification criteria for this hazard class

STOT - Repeated Exposure
Does not meet the classification criteria for this hazard class

Aspiration Hazard
Does not meet the classification criteria for this hazard class

11.2. Information on other hazards
Information not available

12) ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity
Information not available

12.2. Persistence and degradability

2-BUTOXYETHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

2-BUTOXYETHANOL	
Partition coefficient: n-octanol/water	0,81

12.4. Mobility in soil
Information not available

12.5. Results of PBT and vPvB assessment
Information not available

12.6. Other adverse effects
Information not available

13) DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14) TRANSPORT INFORMATION

In accordance with ADR / RID / IMDG / IATA / ADN instructions

	Land transport ADR/RID	**Marine transport IMDG**	**Air transport IATA-DGR**
14.1 UN No	The product is not classified as a dangerous good according to the regulations, regarding its transportation.		
14.2 Description of the goods	Not applicable	Not applicable	Not applicable
14.3 Transport hazard class(es)	Not applicable	Not applicable	Not applicable
14.4 Packaging group	Not applicable	Not applicable	Not applicable
14.5 Environmental hazards	Not applicable	Not applicable	Not applicable

14.6 Special precautions for user
No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable

15) REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
This Safety Data Sheet is prepared according to Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Seveso Category - Directive 2012/18/EC

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Substances subject to authorisation (Annex XIV REACH)

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012

Healthcare control: Information not available

15.2. Chemical safety assessment
A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

16) OTHER INFORMATION

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources: (EC) Regulation 1272/2008 (CLP). ECHA (European Chemicals Agency). Supplier's safety documents.

Full text of H-statements	
H302 - Acute Tox. 4	Harmful if swallowed.
H304 - Asp. Tox. 1	May be fatal if swallowed and enters airways.
H312 - Acute Tox. 4	Harmful in contact with skin.
H315 - Skin Irrit. 2	Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)
with its amendment Regulation (EU) 2015/830

Date of issue : 06.10.2022

KADOL ZBR

SDS No : ***130.01***

Revision date: -

H318 - Eye Dam. 1	Causes serious eye damage.
H319 - Eye Irrit. 2	Causes serious eye irritation.
H332 - Acute Tox. 4	Harmful if inhaled.
H412 - Aquatic Chronic 3	Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Product Safety Data Sheet to their own Product Safety Data Sheet.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary –even for the same product between different countries, reflecting the different compliance requirements.